



**LUBRICANTS  
& FLUIDS  
CATALOGUE**

---

**BSG**  
AUTO PARTS





# INDEX

---

ABOUT US	4-5
ENGINE OILS	6-13
TRANSMISSION, GEAR, STEERING, HYDRAULIC BRAKE OILS	14-24
FLUIDS, ADDITIVES, CAR CARE PRODUCTS	25-31

# ABOUT US

HEADQUARTER  
**Amsterdam,  
NETHERLANDS**

GLOBAL  
WAREHOUSE **18**

WAREHOUSE  
CAPACITY **75.000+ SQM**

# OF  
PRODUCT **50.000+**

WORLDWIDE  
TEAM MEMBERS **1.200+**

**NETHERLANDS**

**TÜRKİYE**

**CHINA**

**U.A.E / DUBAI**

**BSG**  
AUTO PARTS

# ENGINE OILS

---

## Performance Series

Formulated with high-quality base oils and special additives, BSG engine oils, maximize performance of your engine.

While exhibiting excellent performance even under high temperatures and pressures, provides long lasting engine protection.

## 0W-20 DPF

- Fully synthetic engine oil.
- Meets the performance levels required by new generation engines.
- Powerful cleaning agents
- Provides superior protection with its advanced technology.
- Compatible with diesel particulate filters (DPFs) and catalytic converters (CATs) in petrol vehicles.
- Provides superior protection with its low-ash additives.

### PERFORMANCE LEVEL

- API SN/API SM/API SL
- API CF
- ACEA C2-C3 (2012 & 2016)
- BMW LONGLIFE-04
- JAGUAR LAND ROVER ST JLR.03.5004
- MB 229.52/229.51/229.31
- GM DEXOS 2
- FIAT 9. 55535-S3
- PORSCHE C30
- VW 504 00/507 00
- RENAULT RN 0700/RN 0710

### DIMENSIONS:

- 1 L BSG 99-998-075
- 4 L BSG 99-998-076
- 5 L BSG 99-998-077
- 200 L BSG 99-998-078



## 0W-30 DPF

- Fully synthetic engine oil.
- Enhanced frictional properties
- Meets the performance levels required by new generation engines.
- Provides superior protection with its advanced technology.
- Compatible with diesel particulate filters (DPFs) and catalytic converters (CATs) in petrol vehicles.
- Provides superior protection with its low-ash additives.

### PERFORMANCE LEVEL

- API SN/API SM/API SL
- API CF
- ACEA C2-C3 (2012 & 2016)
- BMW LONGLIFE-04
- JAGUAR LAND ROVER ST JLR.03.5004
- MB 229.52/229.51/229.31
- GM DEXOS 2
- FIAT 9. 55535-S3
- PORSCHE C30
- VW 504 00/507 00
- RENAULT RN 0700/RN 0710

### DIMENSIONS:

- 1 L BSG 99-998-069
- 4 L BSG 99-998-070
- 5 L BSG 99-998-071
- 7 L BSG 99-998-072
- 10,5 L BSG 99-998-073
- 11 L BSG 99-998-116
- 200 L BSG 99-998-074



**BSG**  
AUTO PARTS



## 5W-30

- Semi-synthetic engine oil.
- Its oil film layer is resistant to tears.
- Developed to protect the engine in an excellent manner.
- Delivers a prolonged oil change interval

### PERFORMANCE LEVEL

- API SL/CF
- ACEA A3/B4
- VW 501.01/505.00
- MB 229.1
- AVTOVAZ LADA

### DIMENSIONS:

- 1 L BSG 99-998-079
- 4 L BSG 99-998-080
- 5 L BSG 99-998-081
- 7 L BSG 99-998-082
- 10,5 L BSG 99-998-083
- 200 L BSG 99-998-084



Designed by BSG Netherlands

## 5W-30 DPF

- Fully synthetic engine oil.
- Meets the performance levels required by new generation engines.
- Enhanced frictional properties
- Provides superior protection with its advanced technology.
- Excellent low temperature capabilities
- Compatible with diesel particulate filters (DPFs) and catalytic converters (CATs) in petrol vehicles.
- Provides superior protection with its low-ash additives.

### PERFORMANCE LEVEL

- API SN / GF-5
- ACEA C2 / C3-12
- ACEA A5 / B5
- MB 229.51 / MB 229.52 / MB 229.31
- Dexos 1
- Dexos 2
- VW 502.00 / 505.01 / 504.00 / 507.00
- FORD WSS M2C946-A / FORD WSS M2C929-A
- BMW LL04
- PORSCHE C30
- JASO DL-1
- CHRYSLER 6395
- GM 6094 M / GM 4718 M
- HONDA HTO-06

### DIMENSIONS:

- 1 L BSG 99-998-047
- 3,2 L BSG 99-998-048
- 4 L BSG 99-998-049
- 5 L BSG 99-998-050
- 7 L BSG 99-998-051
- 10,5 L BSG 99-998-109
- 11 L BSG 99-998-117
- 200 L BSG 99-998-108



Scan For Approval  
Certificate



**BSG**  
AUTO PARTS

## 5W-40

- Semi-synthetic engine oil.
- Its oil film layer is resistant to tears.
- Increases thermal and oxidation stability
- Developed to protect the engine in an excellent manner.
- Delivers a prolonged oil change interval.
- Lowers oil vaporization and consumption at extreme temperature.

### PERFORMANCE LEVEL

- API SL/CF
- VW 501.01/505.00
- ACEA A3/B3-04
- MB 229.1
- AVTOVAZ LADA

### DIMENSIONS:

- 1 L BSG 99-998-085
- 4 L BSG 99-998-086
- 5 L BSG 99-998-087
- 7 L BSG 99-998-088
- 10,5 L BSG 99-998-089
- 200 L BSG 99-998-090



## 5W-40 DPF

- Fully synthetic engine oil.
- Features a high cleaning power.
- Prevents wear and provides overall performance.
- Environmentally friendly product.
- Developed to extend the life of diesel particulate filters (DPFs) and the catalytic converters (CATs) in petrol vehicles.

### PERFORMANCE LEVEL

- API SN/API SM/API SL
- API CF
- ACEA C2/C3 (2012&2016)
- BMW LONGLIFE-04
- JAGUAR LAND ROVER ST JLR.03.5004
- GM DEXOS 2
- FIAT 9. 55535-S3
- MB 229.52/229.51/229.31
- PORSCHE C30
- VW 507 00 / 504 00
- RENAULT RN0700/RN0710

### DIMENSIONS:

- 3,2 L BSG 99-998-107



## 10W-30

- Semi-synthetic engine oil.
- Formulated with a combination of high performance additives.
- Unrivalled protection in all weather and driving conditions.

### PERFORMANCE LEVEL

- API CI-4/CH-4/CG-4/CF-4/CF
- API SL/SJ
- ACEA E7-16
- ACEA A3/B4-16
- CATERPILLAR ECF-1a
- CUMMINS CES 20076/20077/20078
- Detroit Diesel DDC 93K215
- Deutz DQC-III-10
- JASO DHD-1
- MACK EO-N/EO-M Plus
- MAN M 3275-1
- MB 228.3
- MTU Level 2
- Renault Trucks RDL-2
- VOLVO VDS-3
- Global DHD-1
- ALLISON C4

### DIMENSIONS:

- 1 L BSG 99-998-091
- 4 L BSG 99-998-092
- 5 L BSG 99-998-093
- 7 L BSG 99-998-094
- 10,5 L BSG 99-998-095
- 200 L BSG 99-998-096



**BSG**  
AUTO PARTS



## 10W-40

- Semi-synthetic engine oil.
- Formulated with special additives.
- High-performance multi-grade oil.
- Suitable for use in petrol, diesel and LPG fuelled engines.
- Offers trouble-free and economical performance in all driving conditions.

### PERFORMANCE LEVEL

- API SL/CF
- ACEA A3/B4
- MB 229.1
- VW 501 01
- VW 505 00
- AVTOVAZ LADA

### DIMENSIONS:

- 1 L BSG 99-998-097
- 4 L BSG 99-998-098
- 5 L BSG 99-998-099
- 7 L BSG 99-998-100
- 10,5 L BSG 99-998-101
- 20 L BSG 99-998-129
- 200 L BSG 99-998-102



## 15W-40

- Excellent thermal and oxidation stability.
- High levels of dispersant and detergent properties.
- Prevents wear and contributes to fuel economy.
- Outstanding resistance to foaming, corrosion, and wear.
- Prevents deposit formation and keeps the engine clean.

### PERFORMANCE LEVEL

- API SL/CF
- ACEA A3/B3
- ACEA A3/B4
- FIAT 9.55535-D2
- FIAT 9.55535-G2
- MB 229.1
- PSA B71 2295
- VW 501 01 LEVEL
- VW 505 00 LEVEL

### DIMENSIONS:

- 1 L BSG 99-998-118
- 4 L BSG 99-998-126
- 5 L BSG 99-998-119
- 7 L BSG 99-998-120
- 20 L BSG 99-998-127
- 200 L BSG 99-998-128



## 20W-50

- Mineral engine oil.
- Provides effective performance in petrol, LPG and diesel fuelled engines.
- An engine oil that can be used in all seasons.
- Provides economical and high performance driving under all conditions

### PERFORMANCE LEVEL

- API SL/CF
- ACEA A3/B4
- VW 501.01 / 505.00
- MB 229.1
- AVTOVAZ LADA

### DIMENSIONS:

- 1 L BSG 99-998-103
- 3 L BSG 99-998-130
- 4 L BSG 99-998-104
- 5 L BSG 99-998-105
- 7 L BSG 99-998-131
- 20 L BSG 99-998-132
- 200 L BSG 99-998-106



**BSG**  
AUTO PARTS

# TRANSMISSION, GEAR, STEERING, HYDRAULIC BRAKE OILS

---

BSG Transmission Oils reduces friction, ensures smoother operation of the transmission and minimizes wear

BSG Gear Oils are formulated for effective protection and optimum lubrication in the transmission, differential, gear and gearbox of vehicles under all types of usage and driving conditions

BSG Brake Fluids prevent the rusting of metal parts in the brake system and work in harmony with the plastic-rubber seals and felts in the system

## ATF

- Fully synthetic BSG transmission oil.
- Used only for 6-speed in Transmission.
- Provides fast lubrication performance.
- Prevents loss of time and jerking during gear shifts.
- Provides the highest level of protection for the system.
- Features anti-wear and anti-corrosion properties.
- Provides high thermal and oxidation stability at an excellent level

### PERFORMANCE LEVEL

- VW TL 052 182/VW: G 052/182-513 529
- SEAT AND SKODA (6 SPEED)
- BMW 83 22 2 148 578/83 22 2 148 579
- BMW 83 22 0 440 214/83 22 2 147 477
- FORD/NISSAN R35 SPECIAL - M2C-936-A
- MB 236.21/MB 236.25
- DIA-QUEEN SSTF-I PSA 9734.S2
- PORSCHE:000.043.207.30
- VOLVO 1161838 /1161839
- AUDI/ VW TL 052 529
- FIAT
- FERRARI
- RENAULT
- MITSUBISHI MZ 320065
- RENAULT
- PORSCHE: 000.043.20
- PORSCHE: 000.043.207.29

### DIMENSIONS:

- 1 L BSG 99-998-055



## ATF - LT

- Used in ATF LT 71141 automatic vehicle transmissions.
- Provides a long service life.
- High performance.
- Prolongs transmission lifespan by preventing soot build-up.
- Provides protection against friction.

### PERFORMANCE LEVEL

- PEUGEOT/CITROEN AUTOMOBILES B71 2340
- VOITH TURBO H55.6336.xx
- ZF TE-ML 04D
- ZF TE-ML 11B
- ZF TE-ML 14B
- ZF TE-ML 17C
- MB 236.11

### DIMENSIONS:

- 1 L BSG 99-998-059



**BSG**  
AUTO PARTS

## ATF - CVT

- Formulated for use in CVT transmissions.
- Provides long transmission life and oil performance.
- Offers excellent protection against abrasion.
- Provides ease of shifting gears with its synthetic structure.
- Stabilises heat.
- Prevents foam formation.
- Maintains outstanding steel transmission performance with its friction resistance.
- Provides smooth and loss-free operation of automatic transmissions.

### PERFORMANCE LEVEL

- |          |               |
|----------|---------------|
| - AUDI   | - DODGE       |
| - NISSAN | - MITSUBISHI  |
| - VW     | - SUBARU      |
| - FORD   | - MINI COOPER |
| - HONDA  | - HYUNDAI     |
| - TOYOTA | - SUZUKI      |
| - KIA    | - JEEP        |

### DIMENSIONS:

- 1 L BSG 99-998-056



## ATF - DEXRON II

- Easy gear shifting
- Excellent fluidity at low temperatures
- High resistance to oil film rupture
- Superior wear resistance
- Extended oil change intervals
- Excellent oxidation resistance at high temperatures

### PERFORMANCE LEVEL

- GM Dexron IID
- MAN 339 Type V1
- DTFR 13C100
- GM Allison C4
- CAT TO-2
- ZF 02F/04D/14A/17C
- Voith 55,6355
- Volvo 97340
- Mercon
- TASA

### DIMENSIONS:

- 1 L BSG 99-998-146
- 3 L BSG 99-998-147



## ATF - DEXRON III

- Used in all systems where DEXRON III standard is required.
- Automatic transmission oil.
- Excellent thermal and oxidation stability for long and consistent transmission performance
- Built for automatic gearboxes, torque converters, power steering systems, boat reverse gears, hydrostatic transmissions and hydraulic or mechanical systems requiring DEXRON III standards.

### PERFORMANCE LEVEL

- GENERAL MOTORS DEXRON IIIH
- GM TYPE A SUFFIX A
- MB 236.1, 236.5
- VOITH H55.6335
- ZF TE-ML-02F, 03D, 04D, 09, 11B, 14A, 17C
- GENERAL MOTORS DEXRON IID
- FORD MERCON®
- ALLISON C-4
- MAN 339 TYP Z1, V1
- CAT T0-2

### DIMENSIONS:

- 1 L BSG 99-998-054
- 5 L BSG 99-998-125
- 200 L BSG 99-998-064



## ATF - DEXRON VI

- Used in all systems where DEXRON VI standard is required.
- Automatic transmission oil.
- Flows easily at low temperatures providing good cold-start shifting
- Contains additive to protect automatic transmission hardware
- Built for automatic gearboxes, torque converters, power steering systems, boat reverse gears, hydrostatic transmissions and hydraulic or mechanical systems requiring DEXRON VI standards.

### PERFORMANCE LEVEL

- DEXRON-VI

### DIMENSIONS:

- 1 L BSG 99-998-061
- 5 L BSG 99-998-124
- 200 L BSG 99-998-062



**BSG**  
AUTO PARTS

## SYN 75W-90

- BSG Transmission Oil SYN 75W-90 provides excellent performance in all climatic conditions.
- Makes gear shifting easier, prevents noise generation.
- Used in differential and full transmissions that require performance, operating at high speed/high torque and under heavy load.
- Extends synchromesh life by providing easy gear shifting.
- Provides protection against micron abrasions that may occur on the surface of the parts.
- Reduces operating temperature by minimising friction.

### PERFORMANCE LEVEL

- API GL-5/GL-4
- ZF TE- ML 05A, 7A, 12E
- MAN 342M-1, MAN 342 M-2
- SCANIA STO 1:0
- ZF TE-16B, C AND D, 17B, 19B, 21B
- VOLVO 1273.12
- U.S. STEEL 224
- AGMA 9005-D94
- DIN 51517 PART 3

### DIMENSIONS:

- 1 L BSG 99-998-066
- 3 L BSG 99-998-068



## SYN 75W-80

- BSG Transmission Oil SYN 75W-80 provides excellent performance in all climatic conditions.
- Makes gear shifting easier, prevents noise generation.
- Used in differential and full transmissions that require performance, operating at high speed/high torque and under heavy load.
- Extends synchromesh life by providing easy gear shifting.
- Provides protection against micron abrasions that may occur on the surface of the parts.
- Reduces operating temperature by minimising friction.

### PERFORMANCE LEVEL

- API GL-5/GL-4
- ZF TE- ML 05A, 7A, 12E
- MAN 342M-1, MAN 342 M-2
- SCANIA STO 1:0
- ZF TE-16B, C AND D, 17B, 19B, 21B
- VOLVO 1273.12
- DIN 51517 PART 3
- U.S. STEEL 224
- AGMA 9005-D94

### DIMENSIONS:

- 1 L BSG 99-998-065
- 3 L BSG 99-998-067



## 80W-90

- Thanks to their high content of EP additives, they can withstand extreme loads.
- Due to the sufficient level of EP additives, even if the oil film is ruptured, it prevents metal-to-metal contact during sudden deceleration or rapid acceleration under load.
- Owing to their multigrade properties, they can be used as reliable lubricants in all seasons when properly selected.

### PERFORMANCE LEVEL

- API GL-5
- MB 235.20
- MAN 342 Type M3
- ZF TE-ML 05A/12L/12M/16B/17B/19B/21A

### DIMENSIONS:

- 1 L BSG 99-998-144
- 3 L BSG 99-998-145



## 85W-140

- Reduces oil change frequency, thereby extending oil and equipment life while minimizing disposal costs.
- Reduces wear, consequently increasing production capacity and enhancing equipment performance.
- By reducing oil leakage, consumption, and contamination, it lowers maintenance needs and increases gearbox reliability.
- Maintains performance characteristics even under heavy operating conditions.
- Extends oil and filter change intervals, providing long-lasting oil and equipment life.
- As long as there are no mechanical issues, the anti-foaming additives prevent foaming and cavitation in pumps.

### PERFORMANCE LEVEL

- API GL-5
- MIL-L-2105D
- MB 235.1
- ZF TE-ML 16A,19A
- MAN 341 Z1

### DIMENSIONS:

- 1 L BSG 99-998-154
- 3 L BSG 99-998-155
- 16 L BSG 99-998-156



**BSG**  
AUTO PARTS

## 75W

- Due to their high content of EP additives, they can withstand extreme loads.
- Thanks to the sufficient level of EP additives, even if the oil film is torn, it prevents metal-to-metal contact during sudden deceleration or rapid acceleration under load.
- Owing to their multigrade properties, they can be used as an all-season lubricant when properly selected.

### PERFORMANCE LEVEL

- API GL-5
- MIL-L 2105 C
- PEUGEOT CITROEN ( PSA ) B71 2330

### DIMENSIONS:

- 1 L BSG 99-998-151



## 80W

- Due to their high content of EP additives, they can withstand extreme loads.
- Thanks to the sufficient level of EP additives, even if the oil film is torn, it prevents metal-to-metal contact during sudden deceleration or rapid acceleration under load.
- Owing to their multigrade properties, they can be used as an all-season lubricant when properly selected.

### PERFORMANCE LEVEL

- API GL-5

### DIMENSIONS:

- 1 L BSG 99-998-148
- 3 L BSG 99-998-149



## 90W

- Due to their high content of EP additives, they can withstand extreme loads.
- Thanks to the sufficient level of EP additives, even if the oil film is torn, it prevents metal-to-metal contact during sudden deceleration or rapid acceleration under load.
- Owing to their multigrade properties, they can be used as an all-season lubricant when properly selected.

### PERFORMANCE LEVEL

- API GL-5
- ZF TE-ML 07A, ZF TE-ML 08, ZF TE-ML 16B
- ZF TE-ML 16C, ZF TE-ML 16D, ZF TE-ML 17B
- ZF TE-ML 19B, ZF TE-ML 21A, ZF TE-ML 24A
- MB 235.0
- Voith 3.325-339
- MIL-L-2105D
- DAF

### DIMENSIONS:

- 1 L BSG 99-998-152
- 3 L BSG 99-998-153



## 140W

- Due to their high content of EP additives, they can withstand extreme loads.
- Thanks to the sufficient level of EP additives, even if the oil film is torn, it prevents metal-to-metal contact during sudden deceleration or rapid acceleration under load.
- Owing to their multigrade properties, they can be used as an all-season lubricant when properly selected.

### PERFORMANCE LEVEL

- API GL-4
- U.S. Steel 224
- AGMA 9005-D94
- David Brown S1.53.101(E)
- DIN 51517 Part 3
- ZF TE-ML 02A, 08, 16A, 17A, 19A

### DIMENSIONS:

- 3 L BSG 99-998-150



**BSG**  
AUTO PARTS

## HVI G

- BSG Steering Oil provides high performance in HVI G steering systems.
- A mineral-based power steering oil.
- Produced for power steering systems.
- Protects the entire system against wear, oxidation, corrosion and foaming.
- Lubricates and protects the parts in the system, extends the life of the parts.
- Prevents leakage, noise and rust problems in the system.

### DIMENSIONS:

- 1 L BSG 99-998-052



## HVI R

- BSG Steering Oil provides high performance in HVI R steering systems
- Mineral-based power steering fluid of superior quality.
- Produced for power steering systems.
- Provides full protection.

### DIMENSIONS:

- 1 L BSG 99-998-053



## BRAKE HYDRAULIC OIL DOT 3-DOT 4

- BSG Brake Fluids provides protection against moisture absorption.
- A synthetic brake fluid.
- High performance even at extreme temperatures in brake systems.
- Developed for brake and clutch systems of all cars and motorcycles.

### PERFORMANCE LEVEL

- SAE J1703
- FMVSS 116 DOT 3
- JIS K 2233
- ISO 4925

### DIMENSIONS:

- Dot 3 500 ml BSG 99-998-058
- Dot 4 500 ml BSG 99-998-057



Designed by BSG Netherlands

## HYDRO 46

- Advanced thermal stability,
- Excellent resistance to oxidation,
- Superior protection against wear,
- Excellent filterability,
- Low friction properties,
- Good water separation,
- Effective air release and anti-foaming performance.

### PERFORMANCE LEVEL

- DIN 51524 part II ( HLP )
- Cincinnati P68,69,70 ( ISO VG 32,46,68 for approved)
- Bosch Rexroth RDE 90235
- Eaton M-2950 S/I-286 S3
- Parker HF-0, HF-1, HF-2
- ISO 20763 Conestoga Vane Pump Tests
- JCMAS PO41 HK

### DIMENSIONS:

- 16 L BSG 99-998-142



## HYDRO 68

- Advanced thermal stability,
- Excellent resistance to oxidation,
- Superior protection against wear,
- Excellent filterability,
- Low friction properties,
- Good water separation,
- Effective air release and anti-foaming performance.

### PERFORMANCE LEVEL

- DIN 51524 part II ( HLP )
- Cincinnati P68,69,70 ( ISO VG 32,46,68 for approved)
- Bosch Rexroth RDE 90235
- Eaton M-2950 S/I-286 S3
- Parker HF-0, HF-1, HF-2
- ISO 20763 Conestoga Vane Pump Tests
- JCMAS PO41 HK

### DIMENSIONS:

- 16 L BSG 99-998-143



**BSG**  
AUTO PARTS

## GREEN RUBBER GREASE

- High water resistance
- Adheres to surfaces due to its thixotropic structure, reducing consumption
- Resistant to wear and corrosion
- Provides superior performance in chassis lubrication

### DIMENSIONS:

- 0,9 kg BSG 99-998-133
- 4 kg BSG 99-998-134
- 14 kg BSG 99-998-135



## RED GREASE

- High water resistance
- Adheres to surfaces due to its thixotropic structure, reducing consumption
- Resistant to wear and corrosion
- Provides superior performance in chassis lubrication

### DIMENSIONS:

- 0,9 kg BSG 99-998-136
- 4 kg BSG 99-998-137
- 14 kg BSG 99-998-138



## WHITE LITHIUM GREASE

- High water resistance
- Adheres to surfaces due to its thixotropic structure, reducing consumption
- Resistant to wear and corrosion
- Provides superior performance in chassis lubrication

### DIMENSIONS:

- 0,9 kg BSG 99-998-139
- 4 kg BSG 99-998-140
- 14 kg BSG 99-998-141



**FLUIDS,  
ADDITIVES, CAR  
CARE PRODUCTS**

---

## ANTIFREEZE (BLUE & PURPLE & RED)

BSG Antifreezes; protect the cylinder block/liner, circulation pump, hoses, gaskets in which it circulates against corrosion and resist against freezing in winter and overheating in summer

- -56 °C Red
- -56 °C Blue
- -56 °C Purple
- -26 °C Red
- -26 °C Blue



### DIMENSIONS:

1 L	RED	-56 C	BSG 99-994-005
1,5 L	RED	-56 C	BSG 99-994-001
3 L	RED	-56 C	BSG 99-994-002
5 L	RED	-26 C	BSG 99-994-010
16 L	RED	-56 C	BSG 99-994-007
205 L	RED	-26 C	BSG 99-994-006
205 L	RED	-56 C	BSG 99-994-012
1 L	BLUE	-56 C	BSG 99-994-003
3 L	BLUE	-56 C	BSG 99-994-004
5 L	BLUE	-26 C	BSG 99-994-011
16 L	BLUE	-56 C	BSG 99-994-008
205 L	BLUE	-26 C	BSG 99-994-009
205 L	BLUE	-56 C	BSG 99-994-013
1 L	PURPLE	-56 C	BSG 99-994-014
1,5 L	PURPLE	-56 C	BSG 99-994-015
3 L	PURPLE	-56 C	BSG 99-994-016

## BLUE DRIVE

- Nox Solution for diesel vehicles with SCR



### DIMENSIONS:

- 10 L BSG 99-999-081
- 18 L BSG 99-999-125

Designed by BSG Netherlands

## BRAKE CLEANER SPRAY

- BSG Brake Cleaner Spray, developed for the purpose of cleaning the metal surfaces of motor vehicles.
- The specially designed valve system provides a 360° spray feature.
- It maintains consistent pressure and delivers effective, uninterrupted cleaning performance even when used in upright, horizontal, or upside-down positions.
- Ensures ease of use, especially in narrow and hard-to-reach areas.

### DIMENSIONS:

- 500 ml BSG 99-999-003
- 60 L BSG 99-999-124



## ALL PURPOSE CARE SPRAY

- A multipurpose product for home use, hobby, workshop, vehicle and industry.
- Used in many areas such as hinges, locks, bolts and spanners.
- Lubricates, cleanses, loosens and protects.
- Provides protection against rust and corrosion.
- Removes water and moisture.

### DIMENSIONS:

- 400 ml BSG 99-999-018



## LIQUID GREASE

- Used as a general purpose lubricant with high adhesion.
- Quickly penetrates and lubricates the sprayed area.
- Used as a general lubricant in industrial areas.

### DIMENSIONS:

- 400 ml BSG 99-999-020



**BSG**  
AUTO PARTS

## AIR SENSOR CLEANING SPRAY

- Used for cleaning the air sensor.
- Cleans sensor and heating wires.
- Removes oil residues from the surface.

### DIMENSIONS:

- 200 ml BSG 99-999-046



## CONTACT CLEANING SPRAY

- Cleans electrical and electronic parts from dust, oil and dirt.
- Resistant to external factors such as moisture, rust and corrosion.
- Volatile and leaves no residue on the surface.
- Prolongs the lifespan of parts with regular use.

### DIMENSIONS:

- 200 ml BSG 99-999-047



## AIR INTAKE AND THROTTLE CLEANING SPRAY

- Used for interior and exterior cleaning of carburettor.
- Cleans oil and soot from parts such as intake manifold and throttle valve.
- No oil residue on the surface after product use.

### DIMENSIONS:

- 500 ml BSG 99-999-049



## RADIATOR CLEANING FLUID

- Used for annual maintenance.
- Cleans oil, lime, rust, sludge and sediment in the cooling system.
- Dissolves oil residues caused by cylinder head failure.
- Prevents rusting.
- Prevents overheating after product use.
- Adequate for up to 6 litres of cooling water.
- Does not damage rubber and aluminium parts as it does not contain acid.

### DIMENSIONS:

- 300 ml BSG 99-999-022



## ENGINE FLUSH

- Cleans the soot and deposits inside your engine.
- Makes your engine run healthier.
- Prevents contamination of the new oil.
- Extends the life of your engine and oil.

### DIMENSIONS:

- 300 ml BSG 99-999-024



## BOLT LOCKER (MEDIUM / HIGH FORCE)

- Used for locking nuts, bolts, etc. that will not be removed frequently.
- Resistant to leaks, corrosion, gases, oils and a wide range of chemicals.
- Also used for filling casting cavities.
- Medium force - High Force

### DIMENSIONS:

- 50 ml BSG 99-999-028 Medium Force  
- 50 ml BSG 99-999-029 High Force



**BSG**  
AUTO PARTS



## CONCENTRATED WINDSHIELD WASHER FLUID

- With Concentrated Window Cleaning Soap, the exterior of cars can look more impressive.
- BSG window cleaner offers a safer driving experience for drivers who want their vehicles to have a stylish and clean appearance.
- The glass cleaner provides a wider and clearer field of view in traffic.
- Concentrated glass cleaning soap extends the lifespan of car windows and ensures long-term use with its lasting effect.
- It provides effective hygiene and long-lasting cleanliness.
- The window cleaner delivers an efficient cleaning performance in both winter and summer.
- It is appreciated by vehicle owners and passengers for its pleasant fragrance.

### DIMENSIONS:

- 32 ml BSG 99-993-029



## WINDSHIELD WASHER FLUID

- Provides a clean view on glass, mirror and headlight surfaces with the effect of alcohol.
- Cleans dirt, insect residues and road stains on vehicle glass.
- Does not damage car paint, polish and wiper blades.

### DIMENSIONS:

- 1 L BSG 99-993-030
- 3 L BSG 99-993
- 5 L BSG 99-999



## WINDSHIELD WASHER FLUID – WITH ANTIFREEZE

- High water resistance
- Adheres to surfaces due to its thixotropic structure, reducing consumption
- Resistant to wear and corrosion
- Provides superior performance in chassis lubrication

### DIMENSIONS:

- |                    |                    |
|--------------------|--------------------|
| -36 °C             | -22 °C             |
| 1 L BSG 99-999-004 | 1 L BSG 99-999-001 |
| 5 L BSG 99-999-005 | 3 L BSG 99-999-122 |
|                    | 5 L BSG 99-999-002 |



**BSG**  
AUTO PARTS

**BSG**  
AUTO PARTS

**NETHERLANDS**  
**BSG AUTO PARTS B.V**

Nieuw-Zeelandweg 7,  
1045 AL Amsterdam, The Netherlands  
T: +31 20 2194637  
info@bsgautoparts.com

**TÜRKİYE**  
**BSG OTO YEDEK PARÇA A.Ş.**

Atatürk Mah. Orhan Veli Cad. No:19  
Esenyurt, İstanbul, Türkiye  
T: +90 212 886 90 60  
info@bsgautoparts.com

**U.A.E / DUBAI**  
**BSG AUTO SPARE PARTS**  
**TRADING L.L.C.**

Show Room NO.12, 400 Building,  
Deira, P.O Box 181923, Dubai, U.A.E  
T: +971 4 2277750  
info@bsgautoparts.com

**CHINA**  
**NINGBO BSG AUTO PARTS**  
**INT. TRADE CO.LTD.**

C1006 Hebang Building, No:899 North  
Tiantong Road, Ningbo, China  
T: +86 574 879 11145  
info@bsgautoparts.com